

# Radübersicht Smart/Brabus

		Felgenabmessung	Einpresstiefe	Felgengewicht (kg)	Reifen (CoC)	minimal*	optimal*	maximal*
Stahlfelge	Vorderachse	5Jx15H2	ET24	6,1	185/55 R15 82H	155	165-175	185
	Hinterachse	6Jx15H2	ET-20	6,5	185/55 R15 82H	175	185-195	205
Spinline	Vorderachse	5Jx15H2	ET24	5,1	185/55 R15 82H	155	165-175	185
	Hinterachse	6Jx15H2	ET-20	6,4	185/55 R15 82H	175	185-195	205
Trackline	Vorderachse	6Jx15H2	ET24	7,8	205/50 R15 86H	175	185-195	205
	Hinterachse	7Jx15H2	ET-15,5	7,8	205/50 R15 86H	195	205-215	225
Spikeline	Vorderachse	6.5Jx16H2	ET24	7,6	205/45 R16 83H	185	195-205	215
	Hinterachse	7Jx16H2	ET-20	8,6	205/45 R16 83H	195	205-215	225
Monoblock VI	Vorderachse	7Jx17H2	ET20	8,7	205/40 R17 80H	195	205-215	225
	Hinterachse	8Jx17H2	ET-15	11,4	225/35 R17 82H	215	225-235	245
Runline	Vorderachse	7Jx17H2	ET20	8,7	205/40 R17 80H	195	205-215	225
	Hinterachse	8Jx17H2	ET-15	11,5	225/35 R17 82H	215	225-235	245

\* mögliche Reifenbreiten laut ETRTO (in mm)

From:

<https://www.smart-wiki.net/> - **Smart WIKI**

Permanent link:

<https://www.smart-wiki.net/452/anleitung/rader>

Last update: **2019/03/28 17:09**

